

# IN5300 (SERIES)

**InFocus**  
Bright Ideas Made Brilliant

## Star Quality

Ease of Use - Sophisticated Features  
Elegant Styling - Stunning Image Quality



# IN5300 (SERIES)

## Lasting brightness and color that stays.

The InFocus IN5300 Series delivers superior visual performance with DLP® DarkChip™ Technology, finely tuned with our own Brilliant Color™ enhancement, a maximum brightness of 4000 lumens, and up to WXGA (1280 x 800) resolution for true to life images in vivid detail. The optical lens shift allows for install flexibility, while DisplayLink™ provides instant set-up and hassle-free projection over USB. The series is network-ready and supports full analog and HD video connectivity. From complex spreadsheets to web-based content to HD video, the new InFocus IN5300 series brings star quality to every performance.

### IN5302

XGA (1024 x 768)  
DLP® DARKCHIP™

The InFocus IN5302 is the ideal XGA upgrade projector for facilities which have older XGA technology. The perfect cost effective alternative integrating DLP® reliability to your existing projection system.

### IN5304

WXGA (1280 x 800)  
DLP® DARKCHIP™

The InFocus IN5304 is the perfect WXGA enhancement projector for facilities that are looking to move to the new world of wide projection/images/visuals. The IN5304 embraces the new wide format standard in personal computers and video content.

### Custom Skins

Choose your cover. With options in Matte Black, Matte White, Glossy Black, Walnut, or pre-primed custom skins, the IN5300 series blends beautifully with any décor.

### Digital, Brilliant Colour

The IN5300 delivers a stunning combination of HD resolution and vivid detail in true-to-life colors with the latest DLP® DarkChip™ technology and InFocus' award-winning BrilliantColor™ implementation. For lasting brightness and colour that stays.

### High Resolution XGA/WXGA

Designed for optimal flexibility, the IN5300 series is available in widescreen WXGA (1280 x 800) resolution to match the new wide format standard in personal computers and video content, or XGA (1024 x 768) resolution for legacy installations.



*The days of staring at an industrial looking box with cables on the ceiling has officially ended.*

**Ben Joy**  
InFocus Product Director



**XGA**  
1,024 x 768 PIXELS

**WXGA**  
1,280 x 800 PIXELS

### Rich Connectivity

The IN5300 series features full analogue connectivity with HD15, BNC and component inputs, and HDMI 1.3 for the latest in Computer and HD Video connectivity. Engineered to be Wireless-Ready with LiteShow II, the IN5300 also includes embedded networking and RS232 control for full projector management over the network.

### Unique "Blue Iris" Glow Ring

The exclusive InFocus "Blue Iris" glow ring notifies users - from experienced to novice - when the projector is powering up or down. No more guessing what the "beep" or small "LED" means.

### 24/7 Non-Stop Projection

All new InFocus DLP® projectors are filter-free and are rated for 24/7 fail-safe operation, resulting in less maintenance and hours of worry-free use.

### Crystal Clear Glass

Masterfully crafted glass lenses provide crystal clear, uniform and precise images.

### LiteShow II

The InFocus LiteShow II wireless adapter connects personal computers to InFocus digital projectors wirelessly. The high bandwidth 802.11 b/g connection supports simultaneous transmission of audio along with video/data content, providing a completely wireless multimedia presentation.

### LiteTouch Keypad

The sleek backlit LiteTouch control panel provides one-touch access to the most commonly used projector functions.

### High Performance Optics

Built-in horizontal and vertical lens shift allows mechanical alignment without optical distortion to retrofit legacy installations. Automatic sensors for ceiling detection and keystone means you will have a crisp, square image everytime. Pincushion/Barrel Distortion eliminates image warping and enables the IN5300 to project perfect images even on imperfect surfaces.

### Projector Management


Control at your fingertips. The IN5300's built-in web browser allows network administrators to remotely access and control the projector over standard LAN/WAN. The series is compatible with ProjectorNet 3.0, our free asset management software that enables you to conserve projector lamp life by scheduling On/Off times, and presetting maintenance events and anti-theft security alerts.

### Dynamic Messaging System

Send dynamic messages for instant display to InFocus projectors using the InFocus Dynamic Messaging System (DMS). Perfect for general and important announcements such as schedule changes, weather warnings, breaking news and emergency notifications.

### Horizontal and Vertical Lens Shift

Manual vertical shift - 105% to 125%  
Manual horizontal shift - +/-15% at 105% vertical offset



### Intuitive and Easy to Use Interface


Over 20 years of customer feedback has gone into designing the IN5300's best in class menu system. It is easy to navigate, has 17 standard languages and a unique intuitive flow.

### Unique Cable Management System

The integrated cable management system provides easy access to the rich connector panel, while aligning each cable to the cable router. The result: 100% hidden cables that look as good as the rest of your room.

### SplitScreen™

Project images from 2 sources simultaneously and in a variety of configurations with SplitScreen™ technology. Perfect for viewing multiple presentations, videoconferencing and distance learning.



InFocus Cable Management System

InFocus Optics Laboratory

## Optional Accessories

Projection Screens  
Cables & Adaptors  
Security Lock (SEC-LOCK-01)  
Replacement Lamp (SP-LAMP-053)  
LiteShow II Wireless Adapter (INLITESHOW2)  
Ceiling Mount SP-CEIL-INSTALL  
Remote Commander HW-COMMANDER-2  
Skin Kit / Glossy Black TOP-05-GB  
Skin Kit / Matte White TOP-05-MW  
Skin Kit / Walnut TOP-05-W  
Skin Kit / Primer TOP-05-B

## DisplayLink™

Hassle-free, lightning fast-projection. DisplayLink™ Content over USB technology eliminates the need for bulky VGA cables and allows for computer and image set up in seconds without toggling or cumbersome function key combinations. DisplayLink™ makes projecting simple!

## Warranty

Providing the highest quality products and support is very important to InFocus. The IN5300 series of digital projectors come standard with a 2-year limited factory warranty (including parts and labor) a 6 month limited lamp replacement warranty and 5 year DLP® warranty. Extended product and lamp warranty programs are also available. For more information, please visit: [www.infocus.com/service](http://www.infocus.com/service)



Navigator - 3 Remote

## IN5300 (SERIES) FEATURES

- 2-3 Pull Down
- Auto Keystone
- BrilliantColor™
- Cable Management System
- Centered Lens
- Closed Captions
- Configurable Skins
- Dynamic Messaging
- Electrical H&V Keystone Correction
- Exhaust Vent on the Rear Side
- Freeze Frame with Magnifying Function
- InFocus UI
- Lamp Door on Side
- Logo Capture
- Low Power Standby (<1W)
- Manual Focus and Zoom
- Manual Lens Shift
- Picture-in-Picture
- Pincushion/Barrel Distortion Correction
- Plug & Play (DDC2B)
- Sleep Timer
- SNMP Capable
- Top Access Lamp
- Touchsense Keypad (LiteTouch™)
- USB Key JPG Reader (LitePort™)
- Vertical and Horizontal SplitScreen™
- WEB Browser Control
- Wireless Ready

**InFocus**  
Bright Ideas Made Brilliant

[www.infocus.com](http://www.infocus.com)

**INFOCUS CORPORATE HEADQUARTERS**  
27500 SW Parkway Avenue  
Wilsonville, Oregon 97070-9215, USA  
Phone: (1) 503-685-8888  
Toll Free: (1) 800-294-6400  
Fax: (1) 503-685-8887

**INTERNATIONAL HEADQUARTERS**  
19 Tanglin Road, 7th Floor  
Singapore 247909  
Phone: (65) 6334-9005  
Fax: (65) 6333-4525



©2009 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Bright Ideas Made Brilliant are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. WB\_IN5300\_APAC\_210808. Part Number: MMINFOCUS-0204

# Specifications\*

	IN5302	IN5304
Native Resolution	IN5302 – XGA 1024 x 768 IN5304 – WXGA 1280 x 800	
Maximum Resolution	WXGA (1920 x 1200)	
Display Technology - DMD	IN5302 – DLP® Technology .55" XGA DarkChip™ IN5304 – DLP® Technology .65" WXGA DarkChip™	
Brightness	4000 ANSI Lumens (3,200 lm Eco Mode)	
Lamp Life**	2500 Hrs Eco Mode (2000 Hrs Normal)	
Contrast Ratio	2300:1 Typical	
Audible Noise	29 db Eco Mode (30 db High Power)	
Computer Compatibility	PC, MAC	
Lenses (Std) - Focal Length	22.18 mm at f2.45 ~ 33.27 mm at f2.9	
- Focus Range	5' to greater than 30' (1.5m to 5m)	
	IN5302	IN5304
- Throw Ratio	1.62 - 2.64	1.57 - 2.39
- Zoom Ratio	1.5:1	1.5:1
Lens Shift Type	Manual	
Lens Shift - Vertical	IN5302 – 105% to 125% IN5304 – 105% to 120%	
- Horizontal	+/- 15% at 105% Vertical Offset	
Colorwheel	RGBYW / 5 Segment	
Number of Color	1.07 Billion	
Aspect Ratio	IN5302 – Native 4:3 IN5304 – Native 16:10	
Lamp Configuration	330W	
Zoom/Focus	Manual Focus Manual Zoom	
Synch - Horizontal Scan Freq	15 ~ 100kHz (Video/PC)	
- Vertical Scan Freq	50 ~ 85Hz (Video/PC)	
Video Compatibility	NTSC / PAL / SECAM / PAL-M, N / NTSC4.43 SDTV: 480i, 480p, 576i, 576p HDTV: 720p, 1080i, 1080p (60,30,24Hz)	
Audio	5W x 2	
Input Sources	15pin Dsub x 2, RGBHV BNC, DisplayLink, LitePort HDMI x 2, Component, S-Video Composite Stereo Mini x 2, RCA Stereo x 3	
Output Sources	15pin Dsub Stereo-Mini Jack x 1	
Control - Wired Remote	2.5mm Stereo Mini	
- Control	RS232 Dsub-9, LAN, Wired Remote	
Screen Trigger	3.5mm Mini 12VDC 250ma	
Network	10 BASE-T, 100 BASE-TX	
Product Weight	16.76 lbs / 7.6 kg	
Product Dimensions - WxDxH	14.25 x 21.25 x 7.0 in / 362 x 540 x 178 mm	
Product Colour	Matte Black, Glossy Black, Matte White, Walnut, Primer for Customization	
Remote Control	Navigator - 3	
Ships With - Accessories	RGB Cable, Power Cord, USB Mini-G to A, Remote, Safety Instruction, Projector User's Guide, Display Link User's Guide	
Menu Languages	English, French, German, Italian, Korean, Portuguese, Russian, Spanish, Traditional Chinese, Simplified Chinese, Norwegian, Swedish, Finnish, Danish, Dutch, Polish, Turkish	
Regulatory Model	M5300	
Approvals	UL60950-1/cUL (USA and Canada), FCC Part 15, Class A (USA), CE (Europe), NOM (Mexico), S-Mark (Argentina), GOST (Russia), KC (Korea) SAFETY Mark (Singapore), CCC, CECP (China), C-Tick (Australia/NZ)	
Security	Kensington Lock	

\* Product specifications, terms, and offerings are subject to change at any time without notice.

\*\* Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.